


Bucket technical specification

Round bucket 2.5-1 L

Plastic bucket with lid and handle



Dimensions

D1: ø 185.40 mm
D2: ø 154.80 mm
H: 135.40 mm (134.90 mm bez poklopca)

1. General information & PPWR:

Product name:	Round bucket 2.5-1 L
Product code:	019246
Manufacturer:	PREPLAM d.o.o., Jakovlje, Hrvatska
PPWR classification:	Rigid primary contact-sensitive packaging (Contact-sensitive / B2C & B2B)
Food contact:	yes, in accordance with Commission Regulation (EU) No 10/2011
Intended use (Application):	Food industry

2. Dimensions & geometry:

- Nominal volume: 2.5 L (Brimful volume: 2.6 L)
- Total assembly mass: 84.0 g (optimised in accordance with Article 21 on mass minimisation)

(Bucket body: 65.0 g | Lid: 15.0 g | Plastic handle: 4.0 g)

- Bucket height (H): 135.40 mm (134.90 mm bez poklopca)
- Upper outer diameter: ø 185.40 mm
- Lower outer diameter (D2): ø 154.80 mm
- Average wall thickness: 1.20 mm (minimum functional thickness)

3. Composition & PCR recyclate:

CURRENT ASSEMBLY COMPOSITION (100% PP virgin material):

├── Bucket body (PP-C): 100% Virgin PP-C (65.0 g)

├── Lid (PP-C): 100% Virgin PP-C (15.0 g)

└── Plastic handle (PP): 100% Virgin PP-C (4.0 g)

└── IML Label (PP): 100% Virgin PP coextruded film (homogeneous PP assembly)

- Recycled content share: Currently contains 0% PCR of recycled polymer.

For additional information visit www.preplam.hr or contact us at preplam@preplam.hr.

Date: 20.10.2026. rev. 03 (PPWR)

Zagrebačka cesta 85, 10297 Jakovlje, Croatia
T: +385 1 2499 130 E: preplam@preplam.hr W: www.preplam.hr

Plastics. Made in Croatia.

• Transition for PPWR 2030: Mechanically recycled PP currently has no EFSA approval for direct food contact. Preplam plans to introduce chemically recycled polypropylene (rPP) with mass balance certification (e.g. ISCC PLUS) to achieve the mandatory PPWR quota of 10% by 2030.

4. Mechanical performance:

• Melt viscosity: MFI (MFR): 12 g/10min (according to ISO 1133 at 230°C / 2.16 kg). Standard viscosity for food-contact assemblies.

• Static pressure: Breaking force (Top Load): 147 N (corresponds to a load of 15.0 kg at 23°C according to ISO 8113).


• Thermal load: Hot filling: up to 100°C (stacking only after complete cooling).

• Freezing conditions: Cold resistance: down to -10°C (PP copolymer retains impact resistance).

• Drop resistance (Drop Test): Drop from a height of 1.2 m at 18°C and 0.8 m at -20°C (filled with water/glycol) - no breakage.

CAD drawings and visuals:

Bucket drawing / dimensions:



3D view of finished assembly:



Lid drawing / dimensions:

Image missing: 019246_poklopac.png

5. Design for recycling:

RECYCLASS EVALUATION RESULT	
Total product mass:	**84.0 g**
Polypropylene (PP) mass:	**84.0 g (100%)**
Mass of contaminants (adhesives, paper):	**0 g**
RESULT: CLASS A — Excellent recyclability	

• D4R Classification: Class A (Maximum recyclability). As the bucket, lid, handle and label are made exclusively of polypropylene (mono-material), the assembly is processed into high-purity secondary rPP without need for separation.

• Decoration technology: In-Mold Labeling (IML) without adhesives and chemical solvents.

Zagrebačka cesta 85, 10297 Jakovlje, Croatia
T: +385 1 2499 130 E: preplam@preplam.hr W: www.preplam.hr

Plastics. Made in Croatia.

	• Heavy metals (Article 5 PPWR): Total presence of lead, cadmium, mercury and chromium is below 100 ppm (< 100 mg/kg). • Free from PFAS and SVHC substances: The product does not contain per- and polyfluoroalkyl substances (PFAS) and SVHC substances listed under the REACH Regulation in a concentration exceeding 0.1% by mass.
6. Logistics & storage:	• Storage: Store in a clean, dry and covered area. Avoid prolonged exposure to direct UV radiation and heat sources to prevent degradation of the polymer matrix. Recommended storage temperature is 5°C do 35°C. • Shelf life (Shelf Life): 12 months from the date of delivery subject to compliance with proper storage conditions. • Standard packaging of buckets: 960 pcs (min 40 pcs) / Euro pallet (1200 x 800 mm) • Standard packaging of lids: 1920 pcs in cardboard boxes (800 x 600 x 500 mm)
7. EU Declaration (DoC):	Tvrtka PREPLAM d.o.o. declares under its sole responsibility that the product 'Round bucket 2.5-1 L', šifra '019246' meets all applicable requirements of the Regulation (EU) on packaging and packaging waste (PPWR) and is in compliance with: - Article 5 (Prohibition and restrictions on hazardous substances) - Article 6 (Design for recycling - Class A) - Article 7 (Share of PCR recyclate in contact-sensitive packaging: currently 0% / transition plan to 10% by 2030.) - Article 21 (Packaging mass minimisation to 84.0 g). - Regulation (EU) No 10/2011 on plastic materials and articles intended for food contact (and all its amendments). The technical file supporting this declaration, including reports on recyclate content, migration tests (where applicable) and physical testing, is stored under document number TD-019246-2026-v03 and is kept in the quality control archive for at least 5 years.

Specification approval:

PREPARED BY:	APPROVED BY:
Damir Majerić Production Planner Signature: _____	Duje Klepo Production Manager Signature: _____

Zagrebačka cesta 85, 10297 Jakovlje, Croatia
T: +385 1 2499 130 E: preplam@preplam.hr W: www.preplam.hr

Plastics. Made in Croatia.