


# Bucket technical specification

## Oval bucket 12 L

Plastic bucket with lid and handle




### Dimensions

D1: ø 349.00 mm
D2: ø 307.0 mm
H: 242.50 mm bez poklopca)

### 1. General information & PPWR:

| | |
|---|---|
| **Product name:** | Oval bucket 12 L |
| **Product code:** | 011241 |
| **Manufacturer:** | PREPLAM d.o.o., Jakovlje, Hrvatska |
| **PPWR classification:** | Rigid primary contact-sensitive packaging (Contact-sensitive / B2C & B2B) |
| **Food contact:** | yes in accordance with Commission Regulation (EU) No 10/2011 |
| **Intended use (Application):** | Food industry |

### 2. Dimensions & geometry:

- Nominal volume: 12.0 L (brimful volume: 12.0 L)
- Total assembly mass: 550.4 g (optimised in accordance with Article 21 on mass minimisation)

(Bucket body: 397.0 g | Lid: 95.0 g | Metal handle: 58.4 g)

- Bucket height (H): 242.50 mm bez poklopca)
- Upper outer diameter: ø 349.00 mm
- Lower outer diameter (D2): ø 307.0 mm
- Average wall thickness: 1.20 mm (minimum functional thickness)

### 3. Composition & PCR recyclate:

CURRENT ASSEMBLY COMPOSITION (PP + Metal handle):

├── Bucket body (PP-C): 100% Virgin PP-C (397.0 g)

├── Lid (PP-C): 100% Virgin PP-C (95.0 g)

└── Metal handle: Galvanised steel (galvanised steel wire) - 58.4 g

└── IML Label (PP): 100% Virgin PP coextruded film (homogeneous PP assembly)

- Recycled content share: Currently contains 0% PCR of recycled polymer.



Zagrebačka cesta 85, 10297 Jakovlje, Croatia
T: +385 1 2499 130 E: preplam@preplam.hr W: www.preplam.hr

Plastics. Made in Croatia.

• Transition for PPWR 2030: Mechanically recycled PP currently has no EFSA approval for direct food contact. Preplam plans to introduce chemically recycled polypropylene (rPP) with mass balance certification (e.g. ISCC PLUS) to achieve the mandatory PPWR quota of 10% by 2030.

**4. Mechanical performance:**

• Melt viscosity: MFI (MFR): 12 g/10min (according to ISO 1133 at 230°C / 2.16 kg). Standard viscosity for food-contact assemblies.

• Static pressure: Breaking force (Top Load): 490 N (corresponds to a load of 50.0 kg at 23°C according to ISO 8113).


• Thermal load: Hot filling: up to 90°C (stacking only after complete cooling).

• Freezing conditions: Cold resistance: down to -15°C (PP copolymer retains impact resistance).

• Drop resistance (Drop Test): Drop from a height of 1.2 m at 18°C and 0.8 m at -20°C (filled with water/glycol) - no breakage.

**CAD drawings and visuals:**

**Bucket drawing / dimensions:**




**3D view of finished assembly:**



**Lid drawing / dimensions:**



Zagrebačka cesta 85, 10297 Jakovlje, Croatia
T: +385 1 2499 130 E: preplam@preplam.hr W: www.preplam.hr

Plastics. Made in Croatia.

## 5. Design for recycling:

| RECYCLASS EVALUATION RESULT | |
|---|---|
| Total product mass: | **550.4 g** |
| Polypropylene (PP) mass: | **492.0 g (89.4%)** |
| Mass of detachable metal components: | **58.4 g** |
| Mass of contaminants (adhesives, paper): | **0 g** |
| **RESULT: CLASS B — Good recyclability (detachable metal handle)** | |

• D4R Classification: Class B (Good recyclability). The assembly contains a metal handle. Mechanical and magnetic separation of the metal component from the polypropylene stream is required during recycling.

• Decoration technology: In-Mold Labeling (IML) without adhesives and chemical solvents.

• Heavy metals (Article 5 PPWR): Total presence of lead, cadmium, mercury and chromium is below 100 ppm (< 100 mg/kg).

• Free from PFAS and SVHC substances: The product does not contain per- and polyfluoroalkyl substances (PFAS) and substances from the REACH SVHC list in a concentration exceeding 0.1% by mass.

## 6. Logistics & storage:

• Storage: Store in a clean, dry and covered area. Avoid prolonged exposure to direct UV radiation and heat sources to prevent degradation of the polymer matrix. Recommended storage temperature is 5°C do 35°C.

• Warranty period (Shelf Life): 12 months from the delivery date subject to compliance with proper storage conditions.

• Standard packaging of buckets: 400 pcs (min 40 pcs) / Euro pallet (1200 x 800 mm)

• Standard packaging of lids: 1600 pcs / Euro pallet (1200 x 800 mm)

## 7. EU Declaration (DoC):

Tvrtka PREPLAM d.o.o. declares under sole responsibility that the product 'Oval bucket 12 L', šifra '011241' meets all applicable requirements of the Regulation (EU) on packaging and packaging waste (PPWR) and is in compliance with:

- Article 5 (Prohibition and restrictions of hazardous substances)

- Article 6 (Design for recycling - Class B)

- Article 7 (Share of PCR recyclate in contact-sensitive packaging: currently 0% / transition plan to 10% by 2030.)

- Article 21 (Minimisation of packaging mass to 550.4 g).

- Regulation (EU) No 10/2011 on plastic materials and articles intended for food contact (and all its amendments).



preplam

Zagrebačka cesta 85, 10297 Jakovlje, Croatia

T: +385 1 2499 130 E: preplam@preplam.hr W: www.preplam.hr

The technical file supporting this declaration, including reports on recyclate content, migration tests (where applicable) and physical testing, is stored under document number TD-011241-2026-v01 and is kept in the quality control archive for at least 5 years.

**Specification approval:**

| PREPARED BY: | APPROVED BY: |
|---|---|
| Damir Majerić | Duje Klepo |
| Planning Manager | Production Manager |
| Signature: _____ | Signature: _____ |



Zagrebačka cesta 85, 10297 Jakovlje, Croatia
T: +385 1 2499 130 E: preplam@preplam.hr W: www.preplam.hr

Plastics. Made in Croatia.